

OZNAKA	<b>O11</b> OKNO 160/474
POGLED	<p>The drawing includes three views of a window unit:</p> <ul style="list-style-type: none"> <li><b>Front View:</b> Shows a vertical window with a central fixed pane labeled 'FIKSNO' and two side-hung opening panes above and below. Total height is 4.74m, with a central pane height of 4.45m. Total width is 1.60m, with a central pane width of 1.35m. Spigot heights are 18mm at the top and 11mm at the bottom. Spigot offsets are 10mm and 15mm.</li> <li><b>Side View:</b> Shows the side profile with a total height of 4.74m. It details the opening mechanism with heights of 1.225m, 1.93m, and 1.295m. A top spigot offset of 18mm is shown.</li> <li><b>Cross-section:</b> Shows the window frame and glazing assembly. The total width is 1.60m, with a central pane width of 1.30m and 15mm offsets on each side. The glazing is labeled 'P = 120.00'. Other dimensions include 150.00, 45.00, 5, 20, 20, and 45.</li> </ul>
ZASTEKLITEV	TROSLOJNI TERMOPAN, VARNOSTNO STEKLO
ODPIRANJE	KOMBINIRANO/FIKSNO
OPIS	<ul style="list-style-type: none"> <li>- LESENI PROFILI IZ TERMIČNO MODIFICIRANE SMREKOVINE NATUR ALI MACESEN</li> <li>- MEDSTEKELNI DISTANČNIKI</li> <li>- SKRITO OKOVJE, KLJUKA IZ BRUŠENE NERJAVEČE KOVINE</li> <li>- ALU ZAŠČITNA MASKA NA ZUNANJI STRANI, BARVA PO IZBORU PROJEKTANTA (npr. SVETLO SIVA)</li> <li>- ZASTEKLITEV S TROSLOJNIM TERMOPANOM, VARNOSTNO STEKLO P4A SIST EN 356, REFLEKSNO STEKLO</li> <li>- NOTRANJI ZATEMNITVENI ROLOJI</li> <li>- OKNO OPREMLJENO Z NOTRANJO LESENO IN ZUNANJO PLOČEVINASTO POLICO, BARVA PO IZBORU PROJEKTANTA (npr. SVETLO SIVA)</li> <li>- OKNO <math>U_w \leq 0,9 \text{ W/m}^2\text{K}</math></li> </ul>
ŠTEVILO KOSOV	1