Project: / 02.RD.FD.0100

Revision:
00
Project data
Plan No. : 02.RD.FD.0100

All Revisions
Rebar List according to EN ISO 3776 2003
The bar length is calculated on the basis of the outer contour.

B A R S C H E D U L E Steelgrade: IC_B500B

Pos.	No.	d	Length	D8	D10	D12	D14	D16	D25
1	14	25	8.50						119.00
2	39	25	5.42*						211.38
3	5	16	12.04					60.20	
4	2	16	12.01					24.02	
5	397	16	12.00					4764.00	
6	35	16	11.42*					399.70	
7	136	16	10.01					1361.36	
8	27	16	9.85					265.95	
9	1	16	9.55					9.55	
10	2	16	9.50					19.00	
11	11	16	8.42*					92.62	
12	64	16	8.24					527.36	
13	65	16	7.68*					499.20	
14	71	16	7.34*					521.14	
15	21	16	7.29*					153.09	
16	16	16	7.09*					113.44	
17	40	16	7.00					280.00	
18	3	16	6.95					20.85	
19	3	16	6.94					20.82	
20	14	16	6.79*					95.06	
21	18	16	6.70*					120.60	
22	2	16	6.65					13.30	
23	1	16	6.25					6.25	
24	18	16	6.22*					111.96	
25	15	16	6.06*					90.90	
26	11	16	6.02*					66.22	
27	136	16	5.73*					779.28	
28	3	16	5.66					16.98	
29	176	16	5.61					987.36	
30	136	16	5.10					693.60	
31	15	16	5.10*					76.50	
32	8	16	5.03*					40.24	
33	11	16	4.92*					54.12	
34	17	16	4.71*					80.07	
35	10	16	4.63					46.30	
36	16	16	4.47*					71.52	
37	18	16	4.32					77.76	
38	39	16	4.26*					166.14	
39	1	16	4.26					4.26	
40	5	16	4.06					20.30	
41	8	16	4.00					32.00	
42	1	16	3.90					3.90	
43	2	16	3.85					7.70	
44	1	16	3.65					3.65	
45	13	16	3.55*					46.15	
46	9	16	3.34*					30.06	
47	21	16	3.26*					68.46	
48	1	16	2.97					2.97	
49	30	16	2.85					85.50	

Project: / 02.RD.FD.0100

B A R S C H E D U L E Steelgrade: IC_B500B

Pos.	No.	d	Length	D8	D10	D12	D14	D16	D25
50	1	16	2.70					2.70	
51	27	16	2.31					62.37	
52	97	16	2.28					221.16	
53	39	16	2.24					87.36	
54	158	16	2.01					317.58	
55	213	16	1.98					421.74	
56	116	16	1.20					139.20	
58	100	16	1.20					120.00	
59	40	14	5.61				224.40		
60	10	14	4.53				45.30		
61	20	14	3.50				70.00		
62	500	14	2.62				1310.00		
63	20	14	2.00				40.00		
64	135	14	1.81				244.35		
65	164	14	1.78				291.92		
66	27	12	7.00			189.00			
67	6	12	2.53*			15.18			
68	1920	12	1.72			3302.40			
69	27	10	7.00		189.00				
70	34	10	2.97		100.98				
71	19	8	7.00	133.00					

* = in average

Total lengths	133.00	289.98	3506.58	2225.97	14403.52	330.38
kg / m	D8 0.395	D10 0.617	D12 0.888	D14 1.210	D16 1.580	D25 3.850
kg / d	52.535	178.918	3113.843	2693.424	22757.562	1271.963

Total weight (kg) 30068.245

Project data

Plan No. : 02.RD.FD.0100

All Revisions

Rebar List according to EN ISO 3776 2003

The bar length is calculated on the basis of the outer contour.

B A R S C H E D U L E Steelgrade: IC_B500B with additions

Pos.	No.	d	Length	Verb	D16
57	116	16	1.20	G	139.20

Total lengths	139.20
kg / m	D16 1.580
kg / d	219.936

Total weight (kg) 219.936

P A R T S L I S T Connecting elements

Pos.	No.	Type	Text	Material	Ordernumber
57	116	G_16	Welded	Manufacturer	

G = Thread

Project: / 02.RD.FD.0100

Project data

Plan No. : 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions						
								a	b	c	d	e	R	h
1	25	8.50	14	119.00	7	00		8.50						
								8.50 Comment: sp.						
2	25	--	39	211.38	7	00		6.11						

-a-

Pos.	No.	Length	-a-
1	1	6.11	6.11
2	1	6.07	6.07
3	1	6.04	6.04
4	1	6.00	6.00
5	1	5.96	5.96
6	1	5.93	5.93
7	1	5.89	5.89
8	1	5.86	5.86
9	1	5.82	5.82
10	1	5.78	5.78
11	1	5.75	5.75
12	1	5.71	5.71
13	1	5.67	5.67
14	1	5.64	5.64
15	1	5.60	5.60
16	1	5.57	5.57
17	1	5.53	5.53
18	1	5.49	5.49
19	1	5.46	5.46
20	1	5.42	5.42
21	1	5.38	5.38
22	1	5.35	5.35
23	1	5.31	5.31
24	1	5.28	5.28
25	1	5.24	5.24
26	1	5.20	5.20
27	1	5.17	5.17
28	1	5.13	5.13
29	1	5.09	5.09
30	1	5.06	5.06
31	1	5.02	5.02
32	1	4.99	4.99
33	1	4.95	4.95
34	1	4.91	4.91
35	1	4.88	4.88
36	1	4.84	4.84
37	1	4.80	4.80
38	1	4.77	4.77
39	1	4.73	4.73

Comment:
sp.

3	16	12.04	5	60.20	4	00		12.04						
								12.04 Comment: sp.						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
4	16	12.01	2	24.02	4	00		12.01						

12.01

5	16	12.00	397	4764.00	4	00		12.00						

12.00

Comment:
sp.

6	16	--	35	399.70	4	15		9.57	0.75	6.46				



Pos.	No.	Length	-a-	-b-	-c-
1	1	10.32	9.57	0.75	6.46
2	1	10.39	9.63	0.75	6.50
3	1	10.45	9.70	0.75	6.55
4	1	10.52	9.76	0.75	6.59
5	1	10.58	9.83	0.75	6.63
6	1	10.65	9.89	0.75	6.68
7	1	10.71	9.96	0.75	6.72
8	1	10.78	10.02	0.75	6.76
9	1	10.84	10.09	0.75	6.81
10	1	10.91	10.15	0.75	6.85
11	1	10.97	10.22	0.75	6.90
12	1	11.03	10.28	0.75	6.94
13	1	11.10	10.34	0.75	6.98
14	1	11.16	10.41	0.75	7.03
15	1	11.23	10.47	0.75	7.07
16	1	11.29	10.54	0.75	7.11
17	1	11.36	10.60	0.75	7.16
18	1	11.42	10.67	0.75	7.20
19	1	11.49	10.73	0.75	7.24
20	1	11.55	10.80	0.75	7.29
21	1	11.62	10.86	0.75	7.33
22	1	11.68	10.93	0.75	7.38
23	1	11.75	10.99	0.75	7.42
24	1	11.81	11.06	0.75	7.46
25	1	11.87	11.12	0.75	7.51
26	1	11.94	11.18	0.75	7.55
27	1	12.00	11.25	0.75	7.59
28	1	12.07	11.31	0.75	7.64
29	1	12.13	11.38	0.75	7.68
30	1	12.20	11.44	0.75	7.72
31	1	12.26	11.51	0.75	7.77
32	1	12.33	11.57	0.75	7.81
33	1	12.39	11.64	0.75	7.85
34	1	12.49	11.70	0.79	7.90
35	1	12.56	11.77	0.79	7.94

Comment:
sp.

7	16	10.01	136	1361.36	4	00		10.01						

10.01

Comment:
sp.

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
8	16	9.85	27	265.95	4	15		9.10	0.75	6.43				
								 Comment: sp.						
9	16	9.55	1	9.55	4	00		9.55						
								9.55 Comment: sp.						
10	16	9.50	2	19.00	4	00		9.50						
								9.50 Comment: sp.						
11	16	--	11	92.62	4	00		5.40						
								-a-						

Pos.	No.	Length	-a-
1	1	5.40	5.40
2	1	6.01	6.01
3	1	6.61	6.61
4	1	7.21	7.21
5	1	7.82	7.82
6	1	8.42	8.42
7	1	9.02	9.02
8	1	9.63	9.63
9	1	10.23	10.23
10	1	10.83	10.83
11	1	11.44	11.44

Comment: sp.

12	16	8.24	64	527.36	4	00		8.24						
								8.24 Comment: sp.						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions						
								a	b	c	d	e	R	h
13	16	--	65	499.20	4	15		8.04	0.80	5.69				



Pos.	No.	Length	-a-	-c-
1	1	8.84	8.04	5.69
2	1	8.80	8.00	5.66
3	1	8.77	7.97	5.63
4	1	8.73	7.93	5.61
5	1	8.70	7.90	5.58
6	1	8.66	7.86	5.56
7	1	8.62	7.82	5.53
8	1	8.59	7.79	5.51
9	1	8.55	7.75	5.48
10	1	8.51	7.71	5.45
11	1	8.48	7.68	5.43
12	1	8.44	7.64	5.40
13	1	8.41	7.61	5.38
14	1	8.37	7.57	5.35
15	1	8.33	7.53	5.33
16	1	8.30	7.50	5.30
17	1	8.26	7.46	5.28
18	1	8.22	7.42	5.25
19	1	8.19	7.39	5.22
20	1	8.15	7.35	5.20
21	1	8.12	7.32	5.17
22	1	8.08	7.28	5.15
23	1	8.04	7.24	5.12
24	1	8.01	7.21	5.10
25	1	7.97	7.17	5.07
26	1	7.94	7.14	5.05
27	1	7.90	7.10	5.02
28	1	7.86	7.06	4.99
29	1	7.83	7.03	4.97
30	1	7.79	6.99	4.94
31	1	7.75	6.95	4.92
32	1	7.72	6.92	4.89
33	1	7.68	6.88	4.87
34	1	7.65	6.85	4.84
35	1	7.61	6.81	4.82
36	1	7.57	6.77	4.79
37	1	7.54	6.74	4.76
38	1	7.50	6.70	4.74
39	1	7.46	6.66	4.71
40	1	7.43	6.63	4.69
41	1	7.39	6.59	4.66
42	1	7.36	6.56	4.64
43	1	7.32	6.52	4.61
44	1	7.28	6.48	4.58
45	1	7.25	6.45	4.56
46	1	7.21	6.41	4.53
47	1	7.18	6.38	4.51
48	1	7.14	6.34	4.48
49	1	7.10	6.30	4.46
50	1	7.07	6.27	4.43
51	1	7.03	6.23	4.41
52	1	6.99	6.19	4.38
53	1	6.96	6.16	4.35
54	1	6.92	6.12	4.33
55	1	6.89	6.09	4.30
56	1	6.85	6.05	4.28

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
13														

Pos. No. Length -a- -c-
57 1 6.81 6.01 4.25
58 1 6.78 5.98 4.23
59 1 6.74 5.94 4.20
60 1 6.70 5.90 4.18
61 1 6.67 5.87 4.15
62 1 6.63 5.83 4.12
63 1 6.60 5.80 4.10
64 1 6.56 5.76 4.07
65 1 6.52 5.72 4.05

Comment:
sp.

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
14	16	--	71	521.14	4	00		8.38						

-a-

Pos. No. Length -a-
1 1 8.38 8.38
2 1 8.35 8.35
3 1 8.32 8.32
4 1 8.29 8.29
5 1 8.26 8.26
6 1 8.23 8.23
7 1 8.20 8.20
8 1 8.17 8.17
9 1 8.14 8.14
10 1 8.11 8.11
11 1 8.08 8.08
12 1 8.05 8.05
13 1 8.02 8.02
14 1 8.00 8.00
15 1 7.97 7.97
16 1 7.94 7.94
17 1 7.91 7.91
18 1 7.88 7.88
19 1 7.85 7.85
20 1 7.82 7.82
21 1 7.79 7.79
22 1 7.76 7.76
23 1 7.73 7.73
24 1 7.70 7.70
25 1 7.67 7.67
26 1 7.64 7.64
27 1 7.61 7.61
28 1 7.58 7.58
29 1 7.55 7.55
30 1 7.52 7.52
31 1 7.49 7.49
32 1 7.46 7.46
33 1 7.43 7.43
34 1 7.40 7.40
35 1 7.37 7.37
36 1 7.34 7.34
37 1 7.31 7.31
38 1 7.28 7.28
39 1 7.25 7.25
40 1 7.22 7.22
41 1 7.19 7.19
42 1 7.16 7.16
43 1 7.13 7.13
44 1 7.10 7.10
45 1 7.07 7.07
46 1 7.04 7.04
47 1 7.01 7.01
48 1 6.98 6.98
49 1 6.95 6.95
50 1 6.92 6.92

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
14														

Pos. No. Length -a-
51 1 6.89 6.89
52 1 6.86 6.86
53 1 6.83 6.83
54 1 6.80 6.80
55 1 6.77 6.77
56 1 6.74 6.74
57 1 6.71 6.71
58 1 6.68 6.68
59 1 6.65 6.65
60 1 6.62 6.62
61 1 6.59 6.59
62 1 6.56 6.56
63 1 6.53 6.53
64 1 6.51 6.51
65 1 6.48 6.48
66 1 6.45 6.45
67 1 6.42 6.42
68 1 6.39 6.39
69 1 6.36 6.36
70 1 6.33 6.33
71 1 6.30 6.30

Comment:
sp.

15	16	--	21	153.09	4	00		8.21						

-a-

Pos. No. Length -a-
1 1 8.21 8.21
2 1 8.11 8.11
3 1 8.02 8.02
4 1 7.93 7.93
5 1 7.84 7.84
6 1 7.75 7.75
7 1 7.65 7.65
8 1 7.56 7.56
9 1 7.47 7.47
10 1 7.38 7.38
11 1 7.29 7.29
12 1 7.19 7.19
13 1 7.10 7.10
14 1 7.01 7.01
15 1 6.92 6.92
16 1 6.83 6.83
17 1 6.73 6.73
18 1 6.64 6.64
19 1 6.55 6.55
20 1 6.46 6.46
21 1 6.36 6.36

Comment:
sp.

16	16	--	16	113.44	4	00		1.71						

-a-

Pos. No. Length -a-
1 1 1.71 1.71
2 1 2.43 2.43
3 1 3.15 3.15
4 1 3.86 3.86
5 1 4.58 4.58
6 1 5.30 5.30
7 1 6.01 6.01
8 1 6.73 6.73

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
16								Pos. No. Length -a- 9 1 7.45 7.45 10 1 8.17 8.17 11 1 8.88 8.88 12 1 9.60 9.60 13 1 10.32 10.32 14 1 11.03 11.03 15 1 11.75 11.75 16 1 12.47 12.47 Comment: sp.						
17	16	7.00	40	280.00	4	00		7.00						
								7.00 Comment: sp.						
18	16	6.95	3	20.85	4	00		6.95						
								6.95						
19	16	6.94	3	20.82	4	00		6.94						
								6.94						
20	16	--	14	95.06	4	00		11.44						
								-a- Pos. No. Length -a- 1 1 11.44 11.44 2 1 10.73 10.73 3 1 10.01 10.01 4 1 9.30 9.30 5 1 8.58 8.58 6 1 7.87 7.87 7 1 7.15 7.15 8 1 6.43 6.43 9 1 5.72 5.72 10 1 5.00 5.00 11 1 4.29 4.29 12 1 3.57 3.57 13 1 2.86 2.86 14 1 2.14 2.14 Comment: sp.						
21	16	--	18	120.60	4	00		11.88						
								-a- Pos. No. Length -a- 1 1 11.88 11.88 2 1 11.27 11.27 3 1 10.66 10.66 4 1 10.05 10.05 5 1 9.44 9.44 6 1 8.83 8.83 7 1 8.22 8.22 8 1 7.61 7.61 9 1 7.00 7.00 10 1 6.39 6.39 11 1 5.78 5.78						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
21								Pos. No. Length -a- 12 1 5.17 5.17 13 1 4.56 4.56 14 1 3.95 3.95 15 1 3.34 3.34 16 1 2.73 2.73 17 1 2.12 2.12 18 1 1.51 1.51 Comment: sp.						
22	16	6.65	2	13.30	4	00		6.65						
								6.65						
23	16	6.25	1	6.25	4	00		6.25						
								6.25 Comment: sp.						
24	16	--	18	111.96	4	00	-1	7.92						0.00	0.81
								-a- 81 Pos. No. Length -a- 1 1 8.73 7.92 2 1 8.44 7.63 3 1 8.14 7.33 4 1 7.85 7.03 5 1 7.55 6.74 6 1 7.25 6.44 7 1 6.96 6.14 8 1 6.66 5.85 9 1 6.36 5.55 10 1 6.07 5.26 11 1 5.77 4.96 12 1 5.47 4.66 13 1 5.18 4.37 14 1 4.88 4.07 15 1 4.58 3.77 16 1 4.29 3.48 17 1 3.99 3.18 18 1 3.70 2.88 Comment: sp.						
25	16	--	15	90.90	4	00		1.80						
								-a- Pos. No. Length -a- 1 1 1.80 1.80 2 1 2.41 2.41 3 1 3.02 3.02 4 1 3.62 3.62 5 1 4.23 4.23 6 1 4.84 4.84 7 1 5.45 5.45 8 1 6.06 6.06 9 1 6.67 6.67 10 1 7.28 7.28 11 1 7.89 7.89 12 1 8.50 8.50						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
25														

Pos. No. Length -a-
13 1 9.11 9.11
14 1 9.72 9.72
15 1 10.33 10.33

Comment:
sp.

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
26	16	--	11	66.22	4	00		5.69						

-a-

Pos. No. Length -a-
1 1 5.69 5.69
2 1 5.76 5.76
3 1 5.82 5.82
4 1 5.89 5.89
5 1 5.95 5.95
6 1 6.02 6.02
7 1 6.08 6.08
8 1 6.15 6.15
9 1 6.21 6.21
10 1 6.27 6.27
11 1 6.34 6.34

Comment:
sp.

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
27	16	--	136	779.28	4	00		3.25						

-a-

Pos. No. Length -a-
1 1 3.25 3.25
2 1 3.29 3.29
3 1 3.32 3.32
4 1 3.36 3.36
5 1 3.40 3.40
6 1 3.43 3.43
7 1 3.47 3.47
8 1 3.51 3.51
9 1 3.54 3.54
10 1 3.58 3.58
11 1 3.62 3.62
12 1 3.65 3.65
13 1 3.69 3.69
14 1 3.73 3.73
15 1 3.76 3.76
16 1 3.80 3.80
17 1 3.84 3.84
18 1 3.87 3.87
19 1 3.91 3.91
20 1 3.95 3.95
21 1 3.98 3.98
22 1 4.02 4.02
23 1 4.06 4.06
24 1 4.09 4.09
25 1 4.13 4.13
26 1 4.17 4.17
27 1 4.20 4.20
28 1 4.24 4.24
29 1 4.28 4.28
30 1 4.31 4.31
31 1 4.35 4.35
32 1 4.39 4.39
33 1 4.42 4.42
34 1 4.46 4.46
35 1 4.50 4.50
36 1 4.53 4.53

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
27								Pos. No. Length -a-						
								37 1 4.57 4.57						
								38 1 4.61 4.61						
								39 1 4.64 4.64						
								40 1 4.68 4.68						
								41 1 4.72 4.72						
								42 1 4.75 4.75						
								43 1 4.79 4.79						
								44 1 4.83 4.83						
								45 1 4.86 4.86						
								46 1 4.90 4.90						
								47 1 4.94 4.94						
								48 1 4.97 4.97						
								49 1 5.01 5.01						
								50 1 5.05 5.05						
								51 1 5.08 5.08						
								52 1 5.12 5.12						
								53 1 5.16 5.16						
								54 1 5.19 5.19						
								55 1 5.23 5.23						
								56 1 5.27 5.27						
								57 1 5.30 5.30						
								58 1 5.34 5.34						
								59 1 5.38 5.38						
								60 1 5.41 5.41						
								61 1 5.45 5.45						
								62 1 5.49 5.49						
								63 1 5.52 5.52						
								64 1 5.56 5.56						
								65 1 5.60 5.60						
								66 1 5.63 5.63						
								67 1 5.67 5.67						
								68 1 5.71 5.71						
								69 1 5.74 5.74						
								70 1 5.78 5.78						
								71 1 5.82 5.82						
								72 1 5.85 5.85						
								73 1 5.89 5.89						
								74 1 5.93 5.93						
								75 1 5.96 5.96						
								76 1 6.00 6.00						
								77 1 6.04 6.04						
								78 1 6.07 6.07						
								79 1 6.11 6.11						
								80 1 6.15 6.15						
								81 1 6.18 6.18						
								82 1 6.22 6.22						
								83 1 6.26 6.26						
								84 1 6.30 6.30						
								85 1 6.33 6.33						
								86 1 6.37 6.37						
								87 1 6.41 6.41						
								88 1 6.44 6.44						
								89 1 6.48 6.48						
								90 1 6.52 6.52						
								91 1 6.55 6.55						
								92 1 6.59 6.59						
								93 1 6.63 6.63						
								94 1 6.66 6.66						
								95 1 6.70 6.70						
								96 1 6.74 6.74						
								97 1 6.77 6.77						
								98 1 6.81 6.81						
								99 1 6.85 6.85						
								100 1 6.88 6.88						
								101 1 6.92 6.92						
								102 1 6.96 6.96						
								103 1 6.99 6.99						
								104 1 7.03 7.03						
								105 1 7.07 7.07						
								106 1 7.10 7.10						
								107 1 7.14 7.14						
								108 1 7.18 7.18						
								109 1 7.21 7.21						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
27														

Pos. No. Length -a-
110 1 7.25 7.25
111 1 7.29 7.29
112 1 7.32 7.32
113 1 7.36 7.36
114 1 7.40 7.40
115 1 7.43 7.43
116 1 7.47 7.47
117 1 7.51 7.51
118 1 7.54 7.54
119 1 7.58 7.58
120 1 7.62 7.62
121 1 7.65 7.65
122 1 7.69 7.69
123 1 7.73 7.73
124 1 7.76 7.76
125 1 7.80 7.80
126 1 7.84 7.84
127 1 7.87 7.87
128 1 7.91 7.91
129 1 7.95 7.95
130 1 7.98 7.98
131 1 8.02 8.02
132 1 8.06 8.06
133 1 8.09 8.09
134 1 8.13 8.13
135 1 8.17 8.17
136 1 8.20 8.20

Comment:
sp.

28	16	5.66	3	16.98	4	00		5.66						



29	16	5.61	176	987.36	4	25		0.83	3.95	0.83	0.59	0.59		



Comment:
sp.

30	16	5.10	136	693.60	4	00		5.10						



Comment:
sp.

31	16	--	15	76.50	4	00	-1	5.67						0.00	0.81



Pos. No. Length -a-
1 1 6.48 5.67
2 1 6.28 5.47
3 1 6.09 5.27
4 1 5.89 5.08
5 1 5.69 4.88
6 1 5.49 4.68
7 1 5.30 4.49
8 1 5.10 4.29
9 1 4.90 4.09
10 1 4.71 3.90

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
31														

Pos. No. Length -a-
11 1 4.51 3.70
12 1 4.31 3.50
13 1 4.12 3.30
14 1 3.92 3.11
15 1 3.72 2.91

Comment:
sp.

32	16	--	8	40.24	4	00		2.04						

-a-

Pos. No. Length -a-
1 1 2.04 2.04
2 1 2.90 2.90
3 1 3.75 3.75
4 1 4.61 4.61
5 1 5.46 5.46
6 1 6.31 6.31
7 1 7.17 7.17
8 1 8.02 8.02

Comment:
sp.

33	16	--	11	54.12	4	00		2.04						

-a-

Pos. No. Length -a-
1 1 2.04 2.04
2 1 2.61 2.61
3 1 3.19 3.19
4 1 3.77 3.77
5 1 4.34 4.34
6 1 4.92 4.92
7 1 5.50 5.50
8 1 6.07 6.07
9 1 6.65 6.65
10 1 7.23 7.23
11 1 7.80 7.80

Comment:
sp.

34	16	--	17	80.07	4	00		1.51						

-a-

Pos. No. Length -a-
1 1 1.51 1.51
2 1 1.91 1.91
3 1 2.31 2.31
4 1 2.71 2.71
5 1 3.11 3.11
6 1 3.51 3.51
7 1 3.91 3.91
8 1 4.31 4.31
9 1 4.71 4.71
10 1 5.11 5.11
11 1 5.51 5.51
12 1 5.91 5.91
13 1 6.31 6.31
14 1 6.71 6.71
15 1 7.11 7.11
16 1 7.52 7.52
17 1 7.92 7.92

Comment:
sp.

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h	
35	16	4.63	10	46.30	4	00	-1	3.82						0.00	0.81



Comment:
sp.

36	16	--	16	71.52	4	00	-1	4.15						0.00	0.81



Pos.	No.	Length	-a-
1	1	4.96	4.15
2	1	4.89	4.08
3	1	4.83	4.02
4	1	4.76	3.95
5	1	4.70	3.89
6	1	4.63	3.82
7	1	4.57	3.76
8	1	4.50	3.69
9	1	4.44	3.62
10	1	4.37	3.56
11	1	4.31	3.49
12	1	4.24	3.43
13	1	4.17	3.36
14	1	4.11	3.30
15	1	4.04	3.23
16	1	3.98	3.17

Comment:
sp.

37	16	4.32	18	77.76	4	00		4.32							



Comment:
sp.

38	16	--	39	166.14	4	00		5.51							



Pos.	No.	Length	-a-
1	1	5.51	5.51
2	1	5.44	5.44
3	1	5.38	5.38
4	1	5.31	5.31
5	1	5.25	5.25
6	1	5.18	5.18
7	1	5.12	5.12
8	1	5.05	5.05
9	1	4.98	4.98
10	1	4.92	4.92
11	1	4.85	4.85
12	1	4.79	4.79
13	1	4.72	4.72
14	1	4.65	4.65
15	1	4.59	4.59
16	1	4.52	4.52
17	1	4.46	4.46
18	1	4.39	4.39
19	1	4.32	4.32
20	1	4.26	4.26
21	1	4.19	4.19

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
38								Pos. No. Length -a- 22 1 4.13 4.13 23 1 4.06 4.06 24 1 3.99 3.99 25 1 3.93 3.93 26 1 3.86 3.86 27 1 3.80 3.80 28 1 3.73 3.73 29 1 3.66 3.66 30 1 3.60 3.60 31 1 3.53 3.53 32 1 3.47 3.47 33 1 3.40 3.40 34 1 3.33 3.33 35 1 3.27 3.27 36 1 3.20 3.20 37 1 3.14 3.14 38 1 3.07 3.07 39 1 3.01 3.01 Comment: sp.						
39	16	4.26	1	4.26	4	00		4.26						
								4.26 Comment: sp.						
40	16	4.06	5	20.30	4	00		4.06						
								4.06 Comment: sp.						
41	16	4.00	8	32.00	4	00		4.00						
								4.00						
42	16	3.90	1	3.90	4	00		3.90						
								3.90						
43	16	3.85	2	7.70	4	00		3.85						
								3.85						
44	16	3.65	1	3.65	4	00		3.65						
								3.65 Comment: sp.						
45	16	--	13	46.15	4	00		1.55						
								-a- Pos. No. Length -a- 1 1 1.55 1.55 2 1 1.88 1.88 3 1 2.22 2.22 4 1 2.55 2.55						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
45														

Pos. No. Length -a-
5 1 2.88 2.88
6 1 3.21 3.21
7 1 3.55 3.55
8 1 3.88 3.88
9 1 4.21 4.21
10 1 4.54 4.54
11 1 4.88 4.88
12 1 5.21 5.21
13 1 5.54 5.54

Comment:
sp.

46	16	--	9	30.06	4	00	-1	0.36						0.00	1.45



Pos. No. Length -a-
1 1 1.81 0.36
2 1 2.19 0.75
3 1 2.58 1.13
4 1 2.96 1.51
5 1 3.34 1.90
6 1 3.73 2.28
7 1 4.11 2.67
8 1 4.50 3.05
9 1 4.88 3.44

Comment:
sp.

47	16	--	21	68.46	4	00		2.97							



Pos. No. Length -a-
1 1 2.97 2.97
2 1 3.00 3.00
3 1 3.03 3.03
4 1 3.06 3.06
5 1 3.09 3.09
6 1 3.12 3.12
7 1 3.14 3.14
8 1 3.17 3.17
9 1 3.20 3.20
10 1 3.23 3.23
11 1 3.26 3.26
12 1 3.29 3.29
13 1 3.32 3.32
14 1 3.35 3.35
15 1 3.37 3.37
16 1 3.40 3.40
17 1 3.43 3.43
18 1 3.46 3.46
19 1 3.49 3.49
20 1 3.52 3.52
21 1 3.55 3.55

Comment:
sp.

48	16	2.97	1	2.97	4	00		2.97							



Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
49	16	2.85	30	85.50	4	00		2.85						
								2.85						
50	16	2.70	1	2.70	4	00		2.70						
								2.70						
								Comment: sp.						
51	16	2.31	27	62.37	4	21		0.85	0.61	0.85				
								85 / 61 / 85						
52	16	2.28	97	221.16	4	21		0.85	0.58	0.85				
								85 / 58 / 85						
53	16	2.24	39	87.36	4	21		0.81	0.61	0.81				
								81 / 61 / 81						
54	16	2.01	158	317.58	4	21		0.85	0.31	0.85				
								85 / 31 / 85						
55	16	1.98	213	421.74	4	21		0.85	0.28	0.85				
								85 / 28 / 85						
56	16	1.20	116	139.20	4	00		1.20						
								1.20						
58	16	1.20	100	120.00	4	00		1.20						
								1.20						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
59	14	5.61	40	224.40	4	25		0.83	3.95	0.83	0.59	0.59		
								 Comment: sp.						
60	14	4.53	10	45.30	4	00	-1	3.82						0.00	0.71
								 Comment: sp.						
61	14	3.50	20	70.00	4	00		3.50						
														
62	14	2.62	500	1310.00	4	99								

Nr.	dx	dy	dz	l	>°
1	0.00	0.00	0.00	0.50	90
2	0.50	0.00	0.00	0.56	-90
3	0.50	0.56	0.00	0.50	-90
4	0.50	0.56	0.50	0.56	90
5	0.50	0.00	0.50	0.50	
6	1.00	0.00	0.50		

63	14	2.00	20	40.00	4	00		2.00						
														
64	14	1.81	135	244.35	4	21		0.75	0.31	0.75				
														
65	14	1.78	164	291.92	4	21		0.75	0.28	0.75				
														
66	12	7.00	27	189.00	4	00		7.00						
								 Comment: sp.						

Project: / 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions a	b	c	d	e	R	h
67	12	--	6	15.18	4	00		1.97						

-a-

Pos.	No.	Length	-a-
1	1	1.97	1.97
2	1	2.20	2.20
3	1	2.42	2.42
4	1	2.64	2.64
5	1	2.87	2.87
6	1	3.09	3.09

Comment:
sp.

68	12	1.72	1920	3302.40	4	99	



Nr.	dx	dy	dz	l	>°
1	0.00	0.00	0.00	0.40	90
2	0.40	0.00	0.00	0.26	-90
3	0.40	0.26	0.00	0.40	-90
4	0.40	0.26	0.40	0.26	90
5	0.40	0.00	0.40	0.40	
6	0.80	0.00	0.40		

69	10	7.00	27	189.00	4	00		7.00						

7.00

Comment:
sp.

70	10	2.97	34	100.98	4	00		2.97						

2.97

Comment:
sp.

71	8	7.00	19	133.00	4	00		7.00						

7.00

Comment:
sp.

Project: / 02.RD.FD.0100

Project data

Plan No. : 02.RD.FD.0100

B A R B E N D I N G S C H E D U L E Steelgrade: IC_B500B with additions

Bar-mark	d	Bar length	Total nr.	Total length	d Bend	Shape code	End-hook	Bending dimensions						
								a	b	c	d	e	R	h
57	16	1.20	116	139.20	4	00		1.20						



Partlengths incl. Connecting elements
Begin: G_16 Welded Manufacturer;